

Serving the Hospitality Industry with Advanced IP and Analog Telephony Solutions Worldwide

GR-8106-SPB

GR-8206-SPB

1 or 2 Lines Cordless Handset phone





- 1 or 2 lines cordless handset.
- Full duplex speakerphone.
- Message waiting indicator.
- Customizable hotel logo and service dials.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality,impeccable workmanship and stylish products.

At AEi your satisfaction is our priority.





AEi- Corporate Office

Millbrae, California U.S.A Sales: +1.650.552.9416 sales@aeicommunications.com

AEi- CALA Office

Lima, Peru Sales : +51.9.8257.6251 cala@aeicommunications.com

AEi- Asia Pacific Office

New Taipei City, Taiwan Sales : +886.2.2696.8809 asiapac@aeicommunications.com

AEi- EMEA Office

London, United Kingdom Sales:+44 (0)1753.643736 emea@aeicommunications.com

AEi- Southern Asia Office

Penang, Malaysia Sales: +604.3994341 so.asia@aeicommunications.com

AEi- CEE&CIS Office

RF power: 7 dBm

Standby Time: 240 hrs

Talking Time: 9 hrs

Budva, Montenegro Sales:+3826981251 eastern.europe@aeicommunications.com

1. Features

Handset				
Keys		8206		8106
	 Dial keys 	(0~9, *, #)		(0~9, *, #)
	 Line keys 	Line1, Line2, END		Line, END
	 Function keys 	Hold, Speaker, Volume, 6 Service		Mute, Speaker, Volume, 6 Service
		dial keys		dial keys
Phone Features	One or Two Lin	es	•	6 programmable service dials
	 Call Hold and re 	esume(8206 only)	•	Mute and resume(8106 only)
 Handset, Speaker, and Ringer volume control 			•	Red color message waiting indicator
	 Full duplex spe 	aker phone		for ringing and message waiting
Display Contents	 Main logo 		•	DECT signal status
	 Service dial ico 	ns	•	Line status
	 Battery status: power level, charging status 		•	Firmware Version
DECT Standard	 DECT / CAT iq2.0 compatible 		•	Channel Space: 1728 KHz
	Radio Frequence	cy Range:1880~1930 MHz	•	Bit rate: 1150 Kbit/s
	• EU: 1881.792	ch0)~1897.344(ch9) 10 Channels	•	Modulation: GFSK
	• US: 1921.536	(ch0)~1928.448(ch4) 5 Channels	•	Voice coding: 16 Kbit/s

2. Hardware Specifications

Н	•	-	\sim	-	^	4
п	1			•	-	ч

Display • 1.8" TFT color display

LED Indications

 Message waiting indicator and keypad backlight

Power • 3.7v / 900 mAh Li-ion battery

Charging Time: 5 hrs

Contact pins • 3 contact pins for charging and hook detecting

Size and Weight

Dimensions: 175mm(L) x 50mm(W) x 24mm(H), Weight: 180g(battery included)

JP: 1895.616(ch0)~1902.528(ch4) 5 Channels

Stand Cradle

LED Indications

Handset charging indicators

Power • AC adaptor: Input: 100 ~ 240 VAC, Output: 5.9V / 1A

Jacks • DC jack x 1

Contact pins • 3 c

3 contact pins for charging and hook detecting

Operating Low temperature at 0°C

Size and Weight • Dimensions:106mm(L) x88mm(W) x 97mm(H), Weight: 290g

Dimensions:106mm(L) x88mm(W) x 179mm(H), Weight: 455g (handset included)

3.	Regulatory	USA	EU
_	RF	FCC Part 15D	EN 301406
1	EMI	FCC Part 15B	EN 300386
	SAR		EN 62479
	Safety		EN 60950-1
	EMC		EN 301489-1/6
	RoHS	• Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)
	Temperature	 Storage: Low temperature at -10°C 	High temperature at +60°C

Model:

GR-8106-SPB

GR-8206-SPB





High temperature at +40°C