

SFT-1100

1 or 2 Lines
SIP Phone

SFT-1200



- 1 or 2 lines SIP phone.
- Magnetic hook switch.
- Message waiting indicator.
- Coiled cord with anti-drop string.
- Faceplate with customizable hotel logo.

AEI brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEI** your satisfaction is our priority.



1. Features

	Keys	1200	1100
		<ul style="list-style-type: none"> Dial keys (0~9, *, #) Line keys Line1, Line2 with red color LED Function keys Hold, Mute, Volume 	<ul style="list-style-type: none"> (0~9, *, #) NA Hold, Mute, Volume
Phone Features		<ul style="list-style-type: none"> One or Two Lines Call Hold and resume(1200 only) Handset and ringer volume control 	<ul style="list-style-type: none"> Mute and resume Red color message waiting indicator for ringing and message waiting
Easy Administration		<ul style="list-style-type: none"> Web GUI Auto provisioning via TFTP Phone remote resetting 	<ul style="list-style-type: none"> Firmware upgrade via TFTP Phone status monitoring system
Codec		<ul style="list-style-type: none"> G.711 (a-law, μ-law) 	
Network Protocol		<ul style="list-style-type: none"> HTTP server ToS / VLAN IEEE 802.1 p/q 	<ul style="list-style-type: none"> Static IP, DHCP Client
SIP		<ul style="list-style-type: none"> SIP V2 (RFC3261) 	
Security		<ul style="list-style-type: none"> Web login authentication for web setup MD5 for SIP authentication (RFC2069/ RFC2617) 	
DTMF		<ul style="list-style-type: none"> In-Band / Out-of-Band DTMF(RFC2833) / SIP Info (RFC2976) 	
Voice Quality		<ul style="list-style-type: none"> CNG: Comfortable noise generator Echo canceller: LEC / AEC Jitter buffer/PLC 	
Tones		<ul style="list-style-type: none"> Ring back tone (local), Busy tone, Dial tone 	

2. Hardware Specifications

LED Indications	<ul style="list-style-type: none"> Line keys, Hold, Mute keys, and Message waiting indicator
Power	<ul style="list-style-type: none"> PoE : IEEE 802.3af AC adaptor: Input: 100 ~ 240 VAC, Output: 5.9V / 1A (optional)
Jacks	<ul style="list-style-type: none"> RJ45 10/100 Mbs: LAN port x 1, DC jack x 1, RJ9 Handset jack x 1
Ethernet cable	<ul style="list-style-type: none"> 0.5 feet x 1
Size and Weight	<ul style="list-style-type: none"> Dimensions:200mm(L) x82mm(W) x 52mm(H), Weight: 455g

3. Regulatory

	USA	EU
EMI	FCC Part 15B	EN55032
Safety		EN 60950-1
EMC		EN55024
		EN61000-3-2
		EN61000-3-3
		IEC61000-4-2
		IEC61000-4-3
RoHS	<ul style="list-style-type: none"> Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC) 	
Temperature	<ul style="list-style-type: none"> Storage: Low temperature at -10°C Operating Low temperature at 0°C 	<ul style="list-style-type: none"> High temperature at +60°C High temperature at +40°C

Model:

SFT-1100

SFT-1200

