

VM-6108-S(A)

1 or 2 Lines
Analog Phone

VM-6208-S(A)



- 1 or 2 lines analog phone.
- Magnetic hook switch.
- Full duplex speakerphone.
- 8 customizable service dials.
- Message waiting indicator.
- Faceplate with customizable hotel logo.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



1. Features

Keys	6208	6108
	<ul style="list-style-type: none"> Dial keys (0~9, *, #) Line keys Line1, Line2 with red color LED Function keys Redial, Spekaer, Volume +/-, Hold, Message, 8 service dial keys 	<ul style="list-style-type: none"> (0~9, *, #) NA Redial, Spekaer, Volume +/-, Mute, Message, 8 service dial keys
Phone Features	<ul style="list-style-type: none"> 8 customizable service dials Call Hold and resume(6208 only) Handset, speaker and ringer volume control Redial last call 	<ul style="list-style-type: none"> Mute and resume(6108 only) Red color message key with indicator Ringing indicator

2. Hardware Specifications

LED Indications	<ul style="list-style-type: none"> Line keys(red), HOLD(red)/MUTE(red), SPEAKER(red), and MESSAGE(red) keys
Power	<ul style="list-style-type: none"> Telephone line powered
Jacks	<ul style="list-style-type: none"> RJ14(RJ11) PSTN jack x 1, RJ9 Handset jack x 1
Ring Voltage	<ul style="list-style-type: none"> 40V RMS minimum
Line cord	<ul style="list-style-type: none"> 10 feet x 1
Size and Weight	<ul style="list-style-type: none"> Dimensions: 201mm(L) x132mm(W) x 121mm(H), Weight: 620 g (Low profile) Dimensions: 201mm(L) x132mm(W) x 156mm(H), Weight: 620 g (High profile)

3. Regulatory

	USA	EU
PSTN	Part 68	TBR 21
EMC	FCC Part 15B	EN55032 & EN55024
RoHS	<ul style="list-style-type: none"> Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC) 	
Temperature	<ul style="list-style-type: none"> Storage: Low temperature at -10°C Operating Low temperature at 0°C 	<ul style="list-style-type: none"> High temperature at +60°C High temperature at +40°C

Model:

VM-6108-S(A)

VM-6208-S(A)

