



VM-8108-SMK(A)

1 or 2 Lines  
 Cordless Analog  
 Phone

VM-8208-SMK(A)



- 1 or 2 lines cordless phone.
- Magnetic hook switch.
- Full duplex speakerphone.
- 8 customizable service dials.
- Pair up to 4 cordless remotes.
- Message waiting key with indicator.
- Faceplate with customizable hotel logo.



AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At AEi your satisfaction is our priority.



## 1. Features

### Handset

Keys	8208	8108
	<ul style="list-style-type: none"> <li>Dial keys (0~9, *, #)</li> <li>Line keys Line1, Line2, END</li> <li>Function keys SPEAKER, VOLUME +/-, HOLD, MESSAGE, FRONT DESK, EMERGENCY, and 3 soft keys</li> </ul>	<ul style="list-style-type: none"> <li>(0~9, *, #)</li> <li>Line, END</li> <li>SPEAKER, VOLUME +/-, MUTE, MESSAGE, FRONT DESK, EMERGENCY, and 3 soft keys</li> </ul>
Phone Features	<ul style="list-style-type: none"> <li>One or Two Lines</li> <li>3 hard key and 7 scrollable service dials</li> <li>Call Hold and resume(8208 only)</li> <li>Handset, Speaker, and Ringer volume control</li> </ul>	<ul style="list-style-type: none"> <li>Full duplex speaker phone</li> <li>Mute and resume(8108 only)</li> <li>Red color message waiting indicator for ringing and message waiting</li> </ul>
Display Contents	<ul style="list-style-type: none"> <li>Main logo</li> <li>Service dial list/icons</li> <li>Battery status: power level, charging status</li> </ul>	<ul style="list-style-type: none"> <li>DECT signal status</li> <li>Line status</li> <li>Firmware Version</li> </ul>
DECT Standard	<ul style="list-style-type: none"> <li>DECT / CAT iq2.0 compatible</li> <li>Radio frequency range : 1880~1930 MHz</li> <li>EU : 1881.792(ch0)~1897.344(ch9) 10 channels</li> <li>US : 1921.536(ch0)~1928.448(ch4) 5 channels</li> <li>JP : 1895.616(ch0)~1902.528(ch4) 5 Channels</li> </ul>	<ul style="list-style-type: none"> <li>Channel space : 1728 KHz</li> <li>Bit rate : 1150 Kbit/s</li> <li>Modulation : GFSK</li> <li>Voice coding : 16 Kbit/s</li> <li>RF power : 7 dBm</li> </ul>

### Base

Keys	8208	8108
	<ul style="list-style-type: none"> <li>Dial keys (0~9, *, #)</li> <li>Line keys Line1, Line2 with red color LED</li> <li>Function keys REDIAL, SPEKAER, VOLUME +/-, HOLD, MESSAGE, 8 Service dial keys</li> </ul>	<ul style="list-style-type: none"> <li>(0~9, *, #)</li> <li>N/A</li> <li>REDIAL, SPEKAER, VOLUME +/-, MUTE, MESSAGE, 8 Service dial keys</li> </ul>
Phone Features	<ul style="list-style-type: none"> <li>8 customizable service dials</li> <li>Call Hold and resume(8208 only)</li> <li>Handset, speaker and ringer volume control</li> <li>Redial last call</li> </ul>	<ul style="list-style-type: none"> <li>Mute and resume(8108 only)</li> <li>Red color message key with indicator</li> <li>Ringing indicator</li> <li>Full duplex speaker phone</li> </ul>
DECT Standard	<ul style="list-style-type: none"> <li>DECT / CAT iq2.0 compatible</li> <li>Radio Frequency Range : 1880~1930 MHz</li> <li>EU : 1881.792(ch0)~1897.344(ch9) 10 Channels</li> <li>US : 1921.536(ch0)~1928.448(ch4) 5 Channels</li> <li>JP : 1895.616(ch0)~1902.528(ch4) 5 Channels</li> </ul>	<ul style="list-style-type: none"> <li>Channel Space : 1728 KHz</li> <li>Bit rate : 1150 Kbit/s</li> <li>Modulation : GFSK</li> <li>Voice coding : 16 Kbit/s</li> <li>RF power : 17 dBm</li> </ul>

## 2. Hardware Specifications

### Handset

- |                 |   |                          |
|-----------------|---|--------------------------|
| Display         | • 2.0" TFT color display  |                          |
| LED Indications | • Message waiting indicator and keypad backlight                                |                          |
| Power           | • 3.7v / 900 mAh Li-ion battery   | • Standby Time : 240 hrs |
|                 | • Charging Time : 5 hrs   | • Talking Time: 9 hrs    |
| Contact pins    | • 3 contact pins for charging, hook detecting and auto-pairing                  |                          |
| Size and Weight | • Dimensions: 190mm(L) x 50mm(W) x 16.5mm mm(H), Weight: 140g(battery included) |                          |

### Base

- |                 |  |
|-----------------|--|
| LED Indications | • Line keys(red), HOLD(red)/MUTE(red), SPEAKER(red), and MESSAGE(red) keys |
| Power           | • AC adaptor: Input: 100 ~ 240 VAC, Output: 5V / 1.5A                      |
| Jacks           | • RJ14(RJ11) PSTN jack x 1, DC jack x 1                                    |
| Contact pins    | • 3 contact pins for charging and hook detecting.                          |
| Line cord       | • 10 feet x 1  |
| Size and Weight | • Dimensions: 201mm(L) x132mm(W) x 121mm(H), Weight: 592g (Low profile)    |
|                 | • Dimensions: 201mm(L) x132mm(W) x 156mm(H), Weight: 600g (High profile)   |

## 3. Regulatory

	USA	EU
RF	FCC Part 15D	EN 301406
EMI	FCC Part 15B	EN 300386
SAR		EN 62479
Safety		EN 60950-1
EMC		EN 301489-1/6
RoHS	• Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)	
Temperature	• Storage: Low temperature at -10°C	High temperature at +60°C
	• Operating Low temperature at 0°C	High temperature at +40°C

**Model:**

VM-8108-SMK(A)

VM-8208-SMK(A)

