

AAX-4100

Single Line Analog  
Wall mount Phone



- Single line analog wall mount phone.
- Magnetic hook switch.
- Coiled cord with anti-drop string.
- Faceplate with customizable hotel logo.

**AEI** brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEI** your satisfaction is our priority.





**AEi- Corporate Office**  
 Millbrae, California U.S.A  
 Sales : +1.650.552.9416  
 sales@aeicomcommunications.com

**AEi- CALA Office**  
 Lima, Peru  
 Sales : +51.9.8257.6251  
 cala@aeicomcommunications.com

**AEi- Asia Pacific Office**  
 New Taipei City, Taiwan  
 Sales : +886.2.2696.8809  
 asiapac@aeicomcommunications.com

**AEi- EMEA Office**  
 London, United Kingdom  
 Sales : +44 (0)1753.643736  
 emea@aeicomcommunications.com

**AEi- Southern Asia Office**  
 Penang, Malaysia  
 Sales : +604.3994341  
 so.asia@aeicomcommunications.com

**AEi- CEE&CIS Office**  
 Budva, Montenegro  
 Sales : +3826981251  
 eastern.europe@aeicomcommunications.com

## 1. Features

- |                |  |
|----------------|--|
| Keys           | <ul style="list-style-type: none"> <li>• Dial keys (0~9, *, #)</li> <li>• Function keys Release, Volume</li> </ul>   |
| Phone Features | <ul style="list-style-type: none"> <li>• Single Line</li> <li>• Ring indicator</li> <li>• One key regaining dial tone</li> <li>• One key handset volume control</li> </ul> |

## 2. Hardware Specifications

- |                 |  |
|-----------------|--|
| LED Indications | • Red color ring indicator                             |
| Power           | • Telephone line powered                               |
| Ring Voltage    | • 40V RMS minimum                                      |
| Jacks           | • RJ11 PSTN jack x 1                                   |
| Line cord       | • 0.7 feet x 1   |
| Size and Weight | • Dimensions:200mm(L) x82mm(W) x 46mm(H), Weight: 450g |

## 3. Regulatory

	USA	EU
PSTN	Part 68	TBR 21
EMI	FCC Part 15B	EN55032 & EN55024
RoHS	• Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)	
Temperature	• Storage: Low temperature at -10°C	High temperature at +60°C
	• Operating Low temperature at 0°C	High temperature at +40°C

Serving the Hospitality Industry with Advanced IP and Analog Telephony Solutions Worldwide

**Model:**  
**AAX-4100**

