

VH-6108-S(A)

Single Line  
Analog Phone



- Single line analog phone.
- Hearing aid support.
- Magnetic hook switch.
- Full duplex speakerphone.
- 8 customizable service dials.
- Message waiting indicator.
- Faceplate with customizable hotel logo.

**AEi** brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



## 1. Features

- |                |  |
|----------------|--|
| Keys           | <ul style="list-style-type: none"> <li>• Dial keys (0~9, *, #)</li> <li>• Function keys Volume up/down, Mute, Redial, Message and Guest Service Keys x 8</li> </ul>  |
| Phone Features | <ul style="list-style-type: none"> <li>• Single line telephone system with speakerphone</li> <li>• Adjustable High-low ringer (2 way selectable switch)</li> <li>• 7 steps speakerphone digital volume control</li> <li>• 8 programmable Guest Service Keys and 1 programmable message key</li> <li>• 4 steps handset digital volume control</li> <li>• Multi Purpose LED indicator for Message Waiting and Incoming Ring</li> <li>• Last number redial (Max up to 31 digitals)</li> <li>• Microphone Mute with LED indicator</li> <li>• Hearing Aid Receiver Compatible</li> <li>• PBX / Standard Line compatible</li> <li>• Tone dialing only</li> </ul> |

## 2. Hardware Specifications

- |                 |   |
|-----------------|---|
| Power           | <ul style="list-style-type: none"> <li>• Line Power (without AC adaptor or battery). Operating voltage within 24V~ 60V and current 20mA ~90mA.</li> </ul> |
| Jacks           | <ul style="list-style-type: none"> <li>• RJ11 Jack x 1, RJ9 jack x 1.</li> </ul>  |
| Size and Weight | <ul style="list-style-type: none"> <li>• Dimensions: 208mm x 132mm x 70mm, Weight: 630g</li> </ul>  |

## 3. Regulatory

	USA	EU
PSTN	Part 68	TBR 21
EMC	FCC Part 15B	EN55032 & EN55024
RoHS	<ul style="list-style-type: none"> <li>• Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)</li> </ul>	
Temperature	<ul style="list-style-type: none"> <li>• Storage: Low temperature at -10°C</li> <li>• Operating Low temperature at 0°C</li> </ul>	<ul style="list-style-type: none"> <li>High temperature at +60°C</li> <li>High temperature at +40°C</li> </ul>

**Model:**  
 VH-6108-S(A)

