

VM-9108-SM(A)

1 or 2 Lines
Corded Analog
Phone

VM-9208-SM(A)



- 1 or 2 lines corded analog phone.
- Magnetic hook switch.
- Full duplex speakerphone.
- 8 customizable service dials.
- Pair up to 4 cordless remotes.
- Message waiting key with indicator.
- Faceplate with customizable hotel logo.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



1. Features

Keys	9208	9108
	<ul style="list-style-type: none"> Dial keys (0~9, *, #) Line keys Line1, Line2 with red color LED Function keys REDIAL, SPEKAER, VOLUME +/-, HOLD, MESSAGE, 8 Service dial keys 	<ul style="list-style-type: none"> (0~9, *, #) NA REDIAL, SPEKAER, VOLUME +/-, MUTE, MESSAGE, 8 Service dial keys
Phone Features	<ul style="list-style-type: none"> 8 customizable service dials Call Hold and resume(9208 only) Handset, speaker and ringer volume control Redial last call 	<ul style="list-style-type: none"> Mute and resume(9108 only) Red color message key with indicator Ringing indicator Full duplex speaker phone
DECT Standard	<ul style="list-style-type: none"> DECT / CAT iq 2.0 compatible Radio Frequency Range : 1880~1930 MHz EU: 1881.792(ch0)~1897.344(ch9)10 Channels US: 1921.536(ch0)~1928.448(ch4) 5 Channels JP: 1895.616(ch0)~1902.528(ch4) 5 Channels 	<ul style="list-style-type: none"> Channel Space : 1728 KHz Bit rate : 1150 Kbit/s Modulation : GFSK Voice coding : 16 Kbit/s RF power : 17 dBm

2. Hardware Specifications

LED Indications	<ul style="list-style-type: none"> Line keys(red), HOLD(red)/MUTE(red), SPEAKER(red), and MESSAGE(red) keys
Power	<ul style="list-style-type: none"> AC adaptor: Input: 100 ~ 240 VAC, Output: 5V / 1.5A (optional)
Jacks	<ul style="list-style-type: none"> RJ14(RJ11) PSTN jack x 1, DC jack x 1, RJ9 Handset jack x 1
Line cord	<ul style="list-style-type: none"> 10 feet x 1
Size and Weight	<ul style="list-style-type: none"> Dimensions: 201mm(L) x132mm(W) x 121mm(H), Weight: 620g (Low profile) Dimensions: 201mm(L) x132mm(W) x 156mm(H), Weight: 625g (High profile)

3. Regulatory

	USA	EU
RF	FCC Part 15D	EN 301406
EMI	FCC Part 15B	EN 300386
SAR		EN 62479
Safety		EN 60950-1
EMC		EN301489-1/-6
RoHS	<ul style="list-style-type: none"> Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC) 	
Temperature	<ul style="list-style-type: none"> Storage: Low temperature at -10°C Operating Low temperature at 0°C 	<ul style="list-style-type: none"> High temperature at +60°C High temperature at +40°C

Model:

VM-9108-SM(A)

VM-9208-SM(A)

